	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments
1	BRS	L1	3	(position depth) with (controlling control) and processor and (remote adj control) and (toggle) and (solenoid adj valve) and potentiometer	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2005/09/20 18:03	
2	BRS	L2	4	(position depth) with (controlling control) and (CPY computer processor) and (remote adj control) and (toggle) and (solenoid adj valve) and potentiometer and input	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2005/09/20 18:05	
3	BRS	L3	0	(172/2,4,4.5.ccls. 37/348.ccls. 701/50.ccls.) and (CPU computer processor) and (remote adj control) and (toggle) and (solenoid adj valve) and potentiometer and input	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2005/09/20 18:06	
4	BRS	L4	5	(CPU computer processor) and (remote adj control) and (toggle) and (solenoid adj valve) and potentiometer and input	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2005/09/20 18:07	

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments
5	BRS	L5	14	(CPU computer processor) and (remote with control) and (toggle) and (solenoid adj valve) and potentiometer and input	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	2005/09/20 18:07	